

# SLOPESAVER 292

## PRODUCT DATA SHEET



**Slopesaver** is commonly used as a biodegradable surface stabiliser or '**Soil Saver**' for pre-vegetated slopes. The product is manufactured from woven jute fibre to form a mesh of approximately 10mm x 10mm, which is staked at 1m<sup>2</sup> intervals.

The jute will eventually degrade into an organic mulch after approximately two years, by which time the planted vegetation should have taken its place. The Slopesaver Geojute 292gsm is most commonly used in this application.

| SPECIFICATIONS      |                  |         |             |
|---------------------|------------------|---------|-------------|
| PHYSICAL PROPERTIES | UNITS            | VALUE   | TEST METHOD |
| Composition         | 100% jute fibre  |         |             |
| Mass                | g/m <sup>2</sup> | 292     |             |
| Water Retention     | g/m <sup>2</sup> | 1 300   |             |
| Yarn Diameter       | mm               | 2 - 4   |             |
| Open Area           | %                | 65 - 70 |             |
| Aperture Size       | mm               | 10 x 10 |             |
| Roll Width          | m                | 1.22    |             |
| Roll Length         | m                | 100     |             |
| Mass                | g/m <sup>2</sup> | 292     |             |



To ensure this document contains the most up-to-date technical information available go to [fibertex.com](http://fibertex.com)

+27 31 736 7100 | [salesza@fibertex.com](mailto:salesza@fibertex.com) | [fibertex.com](http://fibertex.com)